FBA **5131**

max.
45
sheets

Extremely powerful office shredder with electronic capacity control and automatic oil injection system for a consistently high shred performance.

Level P-4	4 x 40 mm particle cut (C)
Sheet capacity*:	40-45 34-39
Level P-5	2 x 15 mm particle cut (C)
Sheet capacity*:	25-30 I 21-26
Level P-7	0.8 x 5 mm super micro cut (CCC)
Sheet capacity*:	11-12 9-10



Technical specifications

Volume	180 litres (cabinet)
	140 litres (shred bin)
Power	230 V / 50 Hz**
Motor capacity	1600 Watt single phase motor



Dimensions	1020 x 548 x 590 mm (H x W x D)
Weight	102 kg
ID-No.	11400501

GS certificate-No. DP 10037

Product characteristics

SPS - (Safety Protection System) package: patented, electronically controlled, transparent safety flap in the feed opening as additional safety element; EASY-SWITCH - intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bin is full; electronic door protection via a magnetic proximity switch; double motor protection; ZERO ENERGY standby mode: Complete, automatic disconnection from power supply after 30 minutes. Photo cell controlled automatic start and stop. Patented ECC -Electronic Capacity Control: indication of the used sheet capacity during shredding process. Automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance. Convenient 310 mm feed opening for A3 (lengthwise) or A4 (lengthwise and widthwise). High-quality, paper clip proof cutting shafts from special hardened steel with lifetime guarantee (not applicable for model with 0.8 x 5 mm super micro cut). Particle cut models suitable for shredding the most common CDs/DVDs. Quiet but powerful single phase motor for continuous operation. Sturdy chain drive and fully closed gear box housing. High-quality wooden cabinet, mobile on castors. Convenient environmentally-friendly shred bin (no disposable shred bags required).



^{*} A4 paper 70 g/m² | 80 g/m²

EBA 5131

Features



SOLID STEEL CUTTING SHAFTS

Robust and durable: high-quality paper clip proof cutting shafts with lifetime guarantee under conditions of fair wear and tear (except fine cut model SMC).



PATENTED SAFETY FLAP

Extremely safe: electronically controlled safety flap in the feed opening to keep fingers, ties or other objects away from the cutting shafts.



EASY-SWITCH

Ease of operation: intelligent multifunction switch element with integrated optical signals indicating the operational status. Additional "emergency switch" function.



ELECTRONIC OIL INJECTION

The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.



ECC - ELECTRONIC CAPACITY CONTROL

This electronic feature indicates the used sheet capacity during shredding process to avoid paper jams.



CONVENIENT SHRED BIN

The environmentally-friendly shred bin can be removed easily and cleanly from the cabinet. The bin can be used with or without disposable shred bag.

























certificate no. **DP 10037** dated 25.09.2012



GS Test Certificate

Name and address of the holder of the certificate:

(customer):

Krug & Priester GmbH & Co. KG Simon-Schweitzer-Straße 34

72336 Balingen

Name and address of the

Manufacturer:

see above

Product designation: Paper Shredder

Type: 11400501, 11400502, 11514101

Testing based on: DIN EN 60950-1:2011-01+A12:2011-08

EN 60950-1:2006-04+A11:2009-03+A1:2010-03+A12:2011-02

IEC 60950-1:2005-12+AMD1:2009-12 Information technology equipment – Safety;

Part 1: General requirements

EN 12100-2:2004 Safety of machinery – Basic concepts, general principles for design; Part 2: Technical principles EN ISO 13857:2008 Safety of machinery – Safety distances to prevent hazard zones being

reached by upper and lower limbs

Remarks: This GS Test Certificate replaces the GS Test Certificate

DP 10037 dated 22.03.2010.

The type tested meets the requirements specified in article 21 para. 1 of the German Product Safety Act. The holder of the certificate is entitled to affix the GS mark shown overleaf to the products complying with the type tested. At that, the holder of the certificate shall observe the conditions specified overleaf.

The present certificate including the right to affix the GS mark is valid until: 21.03.2015

Further provisions concerning the validity, the extension of the validity and other conditions are laid down in the Rules of Procedure for Testing and Certification of August 2012.



Signature (Dipl.-Ing. Vogl)

Postal address: Postfach • D-65173 Wiesbaden • Office: Rheinstr. 6-8 • D-65185 Wiesbaden Phone: +49 (0) 611/131-8219 • E-Mail: pruefstelle-dp@bgetem.de 612.17-So/Ho • Test report: A 09194 • Produktschlüsselnummer: 001.1001